

Desktop Thermal Label Printer

Model: WTPTD3405E

Our WTPTD3405E Desktop Thermal Label Printer features an impressive 300 dpi print resolution, ethernet interface and fast print speeds up to 5 inches per second. It also has a large 300 metre ribbon capacity, strong ABS plastic housing and is very easy to operate making it ideal for a wide range of applications where high quality label over-printing is required.

FEATURES

- thermal direct or thermal transfer label printing
- 300 dpi print resolution
- ABS plastic housing
- large ribbon capacity 300 metres
- USB and Ethernet Interface
- 1D and 2D barcode printing
- compatible with EPL, ZPL, ZPLII and DPL printer languages
- gap transmissive sensor (centre fixed)
- black mark reflective sensor (position adjustable)
- real time clock (RTC) on board
- compatible for use with; continuous, die-cut, fan-fold, tag, notched, black mark (outside and inside wound) media types
- Bartender Ultralite label design software

Refer to page 2 for additional specifications and options



SPECIFICATIONS

Model Number	Print Resolution	Max Print Speed	Max Print Width	Overall Dimensions (mm)
WTPTD3405E	300 dpi	127 mm / second	105 mm	204 (W) x 280 (D) x 164 (H)

Specifications may change without notice

Model: WTPTD3405E

OPTIONS

Product Number	Description
BL0606	Thermal Printhead Cleaning Kit
RD5912	External Media Holder
RD5929	Standalone Label Rewinder
TTRB0Ø27	110 mm x 300 m Outside Wax/Resin Ribbon

SPECIFICATIONS

Print Method - Direct Thermal	Yes
Print Method - Thermal Transfer	Yes
Printer Type	Desktop
Print Head Type	Flat Head
Maximum Print Speed	127 mm (5 inches) per second
Maximum Print Width	105 mm (4.16 inches)
Maximum Label Width	112 mm
Maximum Label Roll Size	127 mm (5 inches) OD
Maximum Ribbon Length	300 metres
Maximum Ribbon Width	110 mm
Ribbon Wind Direction	Outside
Ribbon Core Size	25 mm (1 inch)
Communication Type: Parallel Serial USB Ethernet WiFi	Yes Yes Yes No Factory Fitted Option
Bartender Ultralite	Yes
Overall Dimensions (mm)	204 (W) x 280 (D) x 164 (H)
Net Weight	2.5 kg



Specifications may change without notice