

Industrial Thermal Label Printer

Model : WTPTI2414MH2

WTPTI2414MH2 Industrial Thermal Label Printer engineered for high volume label printing. Featuring high print speeds of up to 356 mm (14 inches) per second, heavy duty die cast aluminium design, large 600 m ribbon capacity and a range of interface options.

FEATURES

- thermal direct or thermal transfer label printing
- 203 dpi print resolution
- 3.5" Colour LCD display with 6 button menus
- heavy duty die-cast aluminium design
- large ribbon capacity - 600 metres
- RS232, USB and Ethernet Interface
- USB host for scanner or PC keyboard
- 1D and 2D barcode printing
- compatible with EPL, ZPL, ZPLII and DPL printer languages
- gap transmissive sensor (position adjustable)
- black mark reflective sensor (position adjustable)
- head open sensor
- ribbon end sensor
- compatible for use with; continuous, die-cut, fan-fold, tag, notched, black mark, perforated (outside wound) media types
- Bartender Ultralite label design software

Refer to page 2 for additional specifications and options



SPECIFICATIONS

Model Number	Print Resolution	Max Print Speed	Max Print Width	Overall Dimensions (mm)
WTPTI2414MH2	203 dpi	356 mm / second	104 mm	276 (W) x 502 (D) x 326 (H)

LABELLING EQUIPMENT

LABELS | LABELLING EQUIPMENT | PACKAGING EQUIPMENT
ESL & DIGITAL SIGNAGE | WEIGHING SCALES | POS SYSTEMS
FOOD EQUIPMENT | MAINTENANCE & REPAIRS | HIRE

Specifications may change without notice

0800 800 379
enquiries@wedderburn.co.nz
www.wedderburn.co.nz

Industrial Thermal Label Printer

Model: WTPTI2414MH2

OPTIONS

Product Number	Description
BL0606	Thermal Printhead Cleaning Kit
RD6981	Cutter Module
RD6982	Peel Off Module (includes Rewinder for Backing Paper only)
RD6984	Internal Rewinder for Label Rewinding
RD5929	Standalone label rewinder
RD7043	WiFi Kit

SPECIFICATIONS

Print Method - Direct Thermal	Yes
Print Method - Thermal Transfer	Yes
Printer Type	Industrial
Print Head Type	Flat Head
Maximum Print Speed	356 mm (14 inches) per second
Maximum Print Width	104 mm (4 inches)
Maximum Label Width	114 mm
Maximum Label Roll Size	203.2 mm OD
Maximum Ribbon Length	600 m or 90 mm OD
Maximum Ribbon Width	114 mm
Ribbon Wind Direction	Inside or Outside
Ribbon Core Size	25 mm (1 inch)
Communication Type:	
Parallel	No
Serial	Yes
USB	Yes
Ethernet	Yes
WiFi	Additional Option
Bluetooth	Additional Option (Factory Fitted)
Bartender Ultralite	Yes
Peel & Present	Additional Option
Internal Rewinder	Additional Option
Overall Dimensions (mm)	276 (W) x 502 (D) x 326 (H)
Net Weight	15.6 kg



LABELLING EQUIPMENT

LABELS | LABELLING EQUIPMENT | PACKAGING EQUIPMENT
ESL & DIGITAL SIGNAGE | WEIGHING SCALES | POS SYSTEMS
FOOD EQUIPMENT | MAINTENANCE & REPAIRS | HIRE

Specifications may change without notice

0800 800 379
enquiries@wedderburn.co.nz
www.wedderburn.co.nz