

Thermal Linerless Label Printer

Model: WTPDD2406LL

Desktop Thermal Linerless Label Printer with 203 dpi print resolution and a print speed of up to 150 mm per second. The incorporated cutter module automatically cuts after each print job / label to create clean cut labels with zero waste.

FEATURES

WTPDD2406LL

- thermal direct linerless label printing only
- 203 dpi print resolution
- incorporated label cutter unit
- light weight and small footprint
- 108 mm print width
- Ethernet, RS-232 interface or full-speed USB 2.0 interface
- durable and easy maintenance
- snap-in thermal print head loads in 2 seconds
- easy media loading
- supports 1D/GS1 data bar, 2D/composite codes and QR barcodes
- 32 MB DRAM, 16MB Flash ROM



OPTIONS

Product Number	Description
RD5912	External media roll holder
BL0606	Thermal printhead cleaning kit

SPECIFICATIONS

Model Number	Print Resolution	Max Print Speed	Max Print Width	Overall Dimensions (mm)
WTPDD2406LL	203 dpi	150 mm / second	108 mm	184 (W) x 271 (D) x 167 (H)

Specifications may change without notice

SPECIFICATIONS

Print Method - Direct Thermal	Yes
Print Method - Thermal Transfer	No
Printer Type	Desktop
Print Head Type	Flat Head
Maximum Print Speed	150 mm per second (6 inches per second)
Maximum Print Width	108 mm (4.25 inches)
Maximum Label Width	108 mm
Maximum Label Roll Size	127 mm OD (on a 40 mm ID core)
Communication Type:	
Ethernet	Yes as standard
Parallel	No
Serial	Yes as standard
USB	Yes as standard
Bartender Ultralite	Yes
Overall Dimensions (mm)	184 (W) x 271 (D) x 167 (H)
Net Weight	2.2 kg



Specifications may change without notice