

Thermal Label Printer

Model: ZT230USB

The ZT230™ Thermal Label Printers feature a clever space-saving design, effortless setup, intuitive user operation, and ease of service and maintenance. They have been designed for ease of use, versatility and outstanding value.

FEATURES

ZT230USB

- thermal direct or thermal transfer label printing
- 203 dpi print resolution
- space saving design with unique bi-fold door requires just 4" of opening space and fits easily into tight spaces
- icon-based status LEDs provide immediate and easily visible printer status
- side-loading design eliminates complicated threading when loading supplies
- illuminated moveable sensor is visible through the media for trouble-free sensor-position adjustment
- engineered for print precision with fine-tuned adjustments
- crisp, clean text and barcodes - even on narrow media
- easy, tool-less platen and printhead removal enables simple cleaning and replacement
- simple interchangeable connectivity options enables rapid printer changes and upgrade
- only three common tools needed for basic service
- rugged all-metal case for long-lasting use
- 450m/1476' ribbon capacity for increased operational time and fewer ribbon changes
- graphical user interface for easy printer setup and control
- an intuitive interface makes this printer ideally suited for barcode labelling applications requiring frequent format or printer setting changes

OPTIONS

- Peel - a front-mounted passive peel with no take-up spindle
- Cutter
- Real-time clock (RTC)
- Keyboard display unit (KDU)
- Thermal printhead cleaning kit (Order code BL0606)
- Standalone label rewinder (Order code RD5929)



SPECIFICATIONS

Model Number	Print Resolution	Max Print Speed	Max Print Width	Overall Dimensions (mm)
ZT230USB	203 dpi	152 mm / second	104 mm	242 (W) x 432 (D) x 277 (H)

Specifications may change without notice

SPECIFICATIONS

Print Method - Direct Thermal	Yes
Print Method - Thermal Transfer	Yes
Printer Type	Industrial
Print Head Type	Flat Head
Maximum Print Speed	152 mm (5.98 inches) per second
Maximum Print Width	104 mm (4.09 inches)
Maximum Label Width	114 mm
Maximum Label Roll Size	203 mm OD
Maximum Ribbon Length	450 m
Maximum Ribbon Width	110 mm
Ribbon Wind Direction	Inside
Ribbon Core Size	25 mm ID
Communication Type:	
Serial	Yes
USB	Yes
Bartender Ultralite	Yes
Peel & Present	Additional Option
Overall Dimensions (mm)	242 (W) x 432 (D) x 277 (H)
Net Weight	9.1 kg



Specifications may change without notice

▲ **Labelling Equipment.**

*Weighing Scales. Packaging Equipment. Labelling Equipment.
Labels. Food Equipment. POS Solutions. Maintenance & Repairs.*