

Moisture Analyser

Model : PRXM60HR

User friendly moisture analyser with readabilities starting from 0.1 milligrams. High contrast display for easy reading and an optional printer if needed.

FEATURES

PRXM60HR

- programmable memory for 5 products and their specific settings
- user friendly with key descriptive pictograms
- high contrast, brilliant fluorescent display for easy reading
- high temperature range up to 230°C, temperature increments of 1°C
- easy access sample holder
- results printed in accordance with GLP guidelines
- RS-232 interface
- downloads and updates via the Internet
- fast, accurate results, thanks to versatile control of heat value

OPTIONS

- optional printer (as shown)
- aluminium dish 94 mm - box of 80 (order code WI0046)

Refer to page 2 for specifications



Specifications may change without notice

Weighing Scales. Packaging Equipment. Labelling Equipment.
Labels. Food Equipment. POS Solutions. Maintenance & Repairs.

VARIATIONS & SPECIFICATIONS

Model Number	PRXM60HR
Capacity	124 g
Readability (d)	0.1 mg
Pan Size (mm)	100 mm Diameter
Overall Dimensions (mm)	210 (W) x 170 (D) x 340 (H)
Repeatability (sd)	1 g / 0.1% 10 g / 0.01%
Weighing Units	mg
Non-Linearity (typ)	0.2 mg
Stabilization time (typ)	N/A
Tare Range	Full
Draught Shield	Yes
Calibration	External
Printer Output	RS232
Comparator Function	No
Below Balance Weighing	No
Checkweighing Function	No
Counting Function	No
Percentage Function	Yes
Statistics Function	Yes
Density Determination	Yes
Moisture Analysis	Yes
Communication Protocol	RS232
Operating Temperature	10°C to 30°C
Power	230 V AC Power
Environment Suitability	Dust Free Dry Ambient Temperature
Ingress Protection	None
Weight	6.3 kg
MOISTURE SPECIFICATIONS	
Readability Moisture Content	0.001%
Minimum Sample Weight	0.2 g
Measurement Range	124 g
Measurement Mode	°C
Temperature Range	30°C to 230°C
Increment in Temperature	1°C
Heat Source	Choice of radiation heat, halogen, infrared, dark radiator



Specifications may change without notice