



Price Computing Scale

Model : TSDS781TSSB15K

This IP68 water resistant stainless steel price computing scale, weighs up to 15 kg and features an additional TARE value window in the display. It's easy to use and can be powered by mains power or dry cell batteries which provide more than 600 hours of continuous use. It is trade approved and well suited to many retail applications including Seafood, Butcheries, Delis and Market Stalls.

FEATURES

- legal for trade use (TS1934)
- stainless steel construction
- water resistant with IP68 protection rating
- extremely portable, dry cell operation or mains powered
- programmable tare function
- low power consumption, more than 600 hours continuous use from 4 x C size batteries
- easy to read, high contrast LCD display featuring additional TARE value window
- front operator and rear customer display
- large stainless steel weigh platform
- low battery indication and re-zero functions
- 15 PLU pre set keys, with additional 99 programmable PLU's
- AC/DC power adaptor DC 6V



VARIATIONS

Model Number	Max Capacity	Graduation	Platform Size (mm)	Overall Dimensions (mm)
TSDS781TSSB15K	15 kg	2 g / 5 g	290 (W) x 222 (D)	300 (W) x 340 (D) x 135 (H)

WEIGHING SCALES

LABELS | LABELLING EQUIPMENT | PACKAGING EQUIPMENT
ESL & DIGITAL SIGNAGE | WEIGHING SCALES | POS SYSTEMS
FOOD EQUIPMENT | MAINTENANCE & REPAIRS | HIRE

Specifications may change without notice

0800 800 379
enquiries@wedderburn.co.nz
www.wedderburn.co.nz

Price Computing Scale

Model : TSDS781TSSB15K

ORDER CODES FOR OPTIONS & SPARE PARTS

Order Code	Description
OR0609	6V AC Power Adaptor
OR0792	C Size Batteries (requires 4)

SPECIFICATIONS

Legal for Trade Use	Yes (TS1934)
Scale Type	Bench
Type of Display	Bench Level
Display Panel - Operator	LCD
Display Panel - Customer	LCD
Weighing Units	g, kg
Price Computing Function	Yes
Wrapping Function	No
Label Printer Built-in	No
Label / Receipt Type	N/A
Linerless Labelling	No
Label / Receipt Roll Diameter	N/A
Label / Receipt Paper Width	N/A
Label / Receipt Print Resolution	N/A
Operating Temperature	-10 °C to +40 °C
Power	Battery (4 x C size batteries) Mains Power
Environment Suitability	Dry
Ingress Protection Rating	IP68
Standard Interface	No



Specifications may change without notice

WEIGHING SCALES

LABELS | LABELLING EQUIPMENT | PACKAGING EQUIPMENT
ESL & DIGITAL SIGNAGE | WEIGHING SCALES | POS SYSTEMS
FOOD EQUIPMENT | MAINTENANCE & REPAIRS | HIRE

0800 800 379
enquiries@wedderburn.co.nz
www.wedderburn.co.nz