

Junior Sized Meat Bandsaw

Model : HTBARNESJR

Stainless steel junior meat bandsaw designed for easy cleaning and high output with exceptional safety standards. Ideal for butchers, meat processors, fishmongers and supermarkets.

FEATURES

- full stainless steel smooth grain finish
- blade speed 11 metres per second
- stainless steel top and bottom doors can be removed for ease of thorough cleaning
- plastic removable bone dust tray
- sealed motor compartment eliminates scraps
- upper and lower wheels completely enclosed but readily accessible
- blade guarded above and below the cutting zone
- wrap around top blade guard
- door interlocks ensure machine will not operate with doors in open position
- machine ceases operation within approximately 5 seconds of power being turned off
- waist high, front of table mounted, start and stop buttons
- latch in, twist to release emergency stop switch (in emergency operator can lean against the machine to cease operation), button must be manually released to re-start machine
- 24 volt switching control
- adjustable polyurethane feet for maximum stability
- motor 1.5kw, 240v, single phase
- overall weight 160kg



SPECIFICATIONS

Model Number	Max Product Width (mm)	Max Product Height (mm)	Overall Dimensions (mm)
HTBARNESJR	305	275	670 (W) x 860 (D) x 1725 (H)

FOOD EQUIPMENT

LABELS | LABELLING EQUIPMENT | PACKAGING EQUIPMENT
ESL & DIGITAL SIGNAGE | WEIGHING SCALES | POS SYSTEMS
FOOD EQUIPMENT | MAINTENANCE & REPAIRS | HIRE

Specifications may change without notice

0800 800 379
enquiries@wedderburn.co.nz
www.wedderburn.co.nz

Junior Sized Meat Bandsaw

Model : HTBARNESJR

ADDITIONAL SPECIFICATIONS

Motor:	1.5 kw 240v, 1ph
Drive:	Twin "V" belt drive reduction standard
Electrical Controls:	24v switching control 3 switches: 1 push to start, 1 push to stop and 1 emergency latch-in stop button
Blade Speed:	Up to 11 metres per second Optional speeds available on request
Bandsaw Blade (mm):	2870 x 12 (W) x 3 TPI Optional 4 or 6 TPI
Blade Guides:	Top and bottom guides are interchangeable Tin plated steel with tungsten carbide blade back up Removable for easy cleaning
Blade Tensioning:	Fully automatic with blade tension maintained at all times
Wheels:	Aluminum wheels are lightweight and corrosion resistant Dynamically balanced for vibration free operation Top wheel easily removed for cleaning Automatic blade tensioning ensures true running of the blade at all times Top wheel safety lock minimises likelihood of wheel becoming dislodged from its supports in case of blade breakage
Cutting Clearance (mm):	275 (H) x 305 (W)
Cutting Table (mm):	590 x 810 heavy-duty 2.0 stainless steel Turned down edges for rigidity Fully supported for heavy duty use Heavy-duty nylon table insert promotes longer blade life



Specifications may change without notice

FOOD EQUIPMENT

LABELS | LABELLING EQUIPMENT | PACKAGING EQUIPMENT
ESL & DIGITAL SIGNAGE | WEIGHING SCALES | POS SYSTEMS
FOOD EQUIPMENT | MAINTENANCE & REPAIRS | HIRE

0800 800 379
enquiries@wedderburn.co.nz
www.wedderburn.co.nz