



Weigh Labelling Scale (Bench)

Model: SM5500XB Series

Intelligent weigh labelling scale with capacitive touch screen for operator efficiency and a built-in 10" customer facing full-colour display for effective advertising. Connects to a range of peripheral devices. Trade approved in New Zealand.

FEATURES

- legal for trade use (TS1987)
- 10.1" wide full-colour capacitive operator touchscreen
- 10.1" full colour customer facing display
- · front loading label cassette makes for easy label change
- product related information such as recipes or coupons
- · graphics printing on labels and receipts
- remote diagnostics and support
- helpful on-screen operator prompts
- operator display adjustable angle to suit user / counter
- automatic out-of-level compensation
- virtual level bubble
- low label sensor

OPTIONS

- 7" customer facing display (factory option)
- dynamic linerless label printing with auto cutter (factory option)
- express ordering system
- queue management system
- peripheral information printer
- peripherals for multimedia functionality
- electronic shelf label with smart touch remote PLU selection
- · wireless interface
- back office software



Specifications may change without notice

Weigh Labelling Scale (Bench)

Model: SM5500XB Series

SPECIFICATIONS

Model Number	SM5500XBPS15TD	SM5500XBPS15LTD	SM5500XBCS15TD	SM5500XBCS15LTD	
Maximum Capacity	15 kg				
Graduation	0 - 6 kg x 2 g 6 - 15 kg x 5 g				
Display Panel - Operator	10.1" wide capacitive touchscreen				
Display Panel - Customer	Standard WELCOME! Besond Standard	10.1" WVGA	Optiona	Optional 7" WVGA	
Label / Receipt Labeller Type Roll Diameter Print Width Paper Width	Liner (Die-Cut Labels) 125 mm (max) 70 mm (max) 72 mm (max)	Linerless with Auto-Cutter 95 mm (max) 60 mm (max) 62 mm (max)	Liner (Die-Cut Labels) 125 mm (max) 70 mm (max) 72 mm (max)	Linerless with Auto-Cutter 95 mm (max) 60 mm (max) 62 mm (max)	
Printing Speed	up to 150 mm/second*				
Print Resolution	300 dpi				
Processor	ARM Cortex A9 (iMX6 Dual) Dual Core 1GHz				
Operating System	Linux				
System / Storage Memory	1GB DDR3 SDRAM 1066MHz 32GB SDHC card				
Operating Temperature	- 10 ° C to + 40 ° C				
Standard Interfaces	1 x Ethernet 4 x USB 1 x RJ11				
Net Weight	10.7 kg				
Platform Size (mm)	360 (W) x 285 (D)				
Overall Dimensions (mm)	360	7 (D) x 175 (H)	36	386 472	

^{*} To achieve maximum print speed, high sensitivity thermal paper is required

Specifications may change without notice