

Digital Crane Scale

Model: MS34605T

Digital crane scale with an ultra-bright LED digital display for long range viewing. The MS34605T is a cost effective solution for light to medium capacity overhead weighing.

FEATURES

- bright and easy to read, 5 digit, 38 mm high LED display with programmable brightness
- IP65 powder coated alodined cast aluminium corrosion resistant housing
- superior quality Crosby 360° non-bearing swivel
- 200% safe overload and 500% ultimate overload of rated capacity
- user programmable multifunction switch for use as TEST, UNIT select, NET/GROSS, TOTAL (auto or manual), PEAK HOLD and SETPOINTS
- off, Lo, Hi-1, Hi-2 selectable filtering
- maintains two counters. The first counts number of lifts for maintenance records and the second counts overloads for safety warnings
- auto off mode can be programmed for 15, 30, 45, 60 minutes or off
- auto sleep mode; powers down during non-use and powers up with weight change or any key press
- 6 V rechargeable battery power for up to 50 hours operating time
- includes 115/230 VAC rapid charge battery charger
- 2000 3750 divisions standard resolution (up to 10,000d available)
- precision +/- 0.1% + 1d accuracy of applied load
- units of measure lb or kg
- operating temperature range -4° +122°F (-20° to +50° C)

OPTIONS

- RF remote controller (control for On/Off, Zero, Tare and other functions)
 15 m range
- audible setpoint alarm
- MS8000 RF wireless remote display & modem kit (must be factory fitted)



WIRELESS REMOTE DISPLAY



VARIATIONS

Model Number	Max Capacity	Graduation	Overall Dimensions (mm)	
MS34605T	5,000 kg	2 kg	228 (W) x 322 (D) x 423 (H)	

Specifications may change without notice

Model: MS34605T

SPECIFICATIONS

Legal for Trade Use	No
Scale Type	Overhead
Display Type	Digital LED
Display Size	38 mm high
Display Range	Single
2nd Remote Display	Optional
Weighing Units	kilograms, pounds, kilo-newtons, tons, metric tons
Hook and Shackle Included	Yes
Hook Type	Swivel
Safe Overload Rating	200% of rated capacity
Ultimate Overload Rating	500% of rated capacity
RF Functionality	Optional
Remote Control Included	Optional
Battery Type	Rechargeable Battery
Environment Suitability	Dry



Capacity	Resolution	А	В	С	D	E	F	Approximate Shipping Weight
10,000lb	5.0 lb	16.67 in	2.45 in	3.40 in	2.5 in	1.81 in	1.61 in	39 lb
5000kg	2.0 kg	423 mm	62 mm	86 mm	64 mm	46 mm	41 mm	18 kg

Specifications may change without notice