



**MODEL: LX-5600** 

Revolutionising backroom operations, the LX-5600 is DIGI's world-first fully integrated tray sealer capable of trade-approved weighing, gas flushing, top sealing and labelling fresh food.



DIGI's LX-5600 tray sealers unlock the performance potential of your backroom with efficiency, economic and ecological impact.

The LX-5600 breaks new ground as a world first fully automatic tray sealer capable of trade approved weighing, top tray sealing and labelling fresh food in one quick pass.

Extend shelf life, minimise spoilage, safeguard food safety and delight your customers with leakproof packaging. LX-5600 Weigh-Seal-Label machines deliver all that in one compact package that saves on floor space, packaging film, power consumption and food-safe gas.

Time saving design means operators can easily switch between gases for each PLU, and change moulds quickly without specialised training.



### **Prolonged Food Freshness**

MAP gas-flush technology maintains food freshness and extends shelf life with substantial benefits including; reducing the need for discounting product due to imminent expiration dates, minimising expired food in store, reducing food waste, improving customer satisfaction as they have longer to fully consume purchases with minimal spoilage.



### Easy & Simple Mould Change

LX-5600's tool-less mould change process is quick and intuitive eliminating the need for special operator training. Mould trays are compact and lightweight with a convenient integrated storage space to ensure spare moulds are always on hand.



### **Premium Presentation**

In addition to reducing food spoilage and improving food safety, the LX-5600 delivers premium leakproof packaging that heightens consumer appeal and confidence that ultimately increases your brand value and turnover.



Specifications may change without notice

Model: LX-5600

### Efficient, Economical & Ecological


Designed for operational efficiency whilst minimising both running costs and environmental impact, LX-5600's eliminate the need for a vacuum pump and compressor. When compared with conventional MAP machines, LX-5600's have a lower power consumption and use less food-safe gas through gas flushing technology.



### **Compact Footprint**

With a small footprint of just 1.3 m<sup>2</sup>, the LX-5600 is as compact as it is impressive and will easily fit into backroom environments, maximising space and efficiency.





### **Features Overview**

- legal for trade-use weighing (TS2176)
- · weigh, gas flush, top seal and label fresh foods in seconds
- seal up to 17 packs per minute (time depends on film, gas and tray size)
- automatically trims and rewinds film salvage
- easy and simply mould change
- integrated mould storage
- large 15" full colour touch screen
- small footprint of just 1.3 m<sup>2</sup> allows for flexible installation layouts, easily fitting into backroom spaces
- several labeller options: single, double or triple. Time and label costs are saved through multiple labelling options as two or three labels are applied all in one pass when the tray is weighed and sealed
- supplied with two gas tanks as standard
- easily switch between two types of gases for each PLU
- PLU can be programmed with the correct gas type or no gas
- linerless labelling and die-cut label models available



Specifications may change without notice

Model: LX-5600

### Gas Setting Per PLU

Easily switch between two types of gases for different PLUs. PLU can be programmed with the chosen gas type or no gas.

### **Multiple Labelling Options**

In addition to the main labeller, you have the options for a factory-fitted second POP and bottom labeller enabling simultaneous application of up to three labels per tray.

### **Energy-Saving**

Advanced gas flushing technology reduces the amount of food-safe gas required.

Lower power consumption compared with equipment that requires a vacuum pump and compressor.

### Mould Storage

Convenient interior mould storage space means moulds are always on hand.

### Compact

A small footprint of just 1.3 m<sup>3</sup> allows for flexible installation layouts and easily fits into backroom spaces.

### **Easy Mould Change**

Tool-less mould change and compact lightweight design means operators can change between moulds quickly and with minimal effort.

### Minimise 3 Major In-Store Losses by Extending Shelf Life



DISPOSAL LOSS due to extended availability on the shelves



DISCOUNT LOSS from product approaching expiration dates



SALES OPPORTUNITY LOSS with shelves constantly stocked from store opening to closing.









Specifications may change without notice

Model: LX-5600

#### **SPECIFICATIONS**

Weighing Capacity: 6 / 15 kg x 2 / 5 g (multi-interval) Mould sizes (mm): Standard 9x7 220 (W) x 170 (D) Standard 11x7 270 (W) x 170 (D) 15 - 90 Height Custom moulds available on request with the following min/max possible sizes: 200 (W) x 120 (D) x 15 (H) Minimum Maximum 300 (W) x 210 (D) x 90 (H). Packing speed: Top Seal Only: Maximum 17 packs per minute\* Gas Flushing: Estimated 8 - 12 packs per minute\* \* Packing speeds vary depending on tray size, film and gas fill time Film Width (mm) 260 - 360 Film Diameter (mm) 250 Max Main & POP Labels: Thermal Linerless Thermal Die-Cut Label Width (mm): 44 - 59 40 - 80 28 - 105 28 - 105 Label Length (mm): Bottom Label: Label Width (mm): 44 - 59 Label Length (mm): 40 - 105 Display Panel: 15 inch TFT colour touch panel PLU no., commodity name, ingredient, unit price, price, tare weight, best-before-date, use-by-date, Programmable Items: department name, barcode (EAN, 2D), target weight, special message, advertising message, shop name & logo, extra print format etc. Single phase, 200 - 240 V, 50 Hz, 6 A Power requirement: Overall dimensions (mm): 1050 (W) x 1224 (D) x 1443 (H)


#### **FRONT VIEW**

Net weight:


## 

#### LEFT VIEW

Approximately 230 kg



#### **RIGHT VIEW**



Specifications may change without notice

### PACKAGING EQUIPMENT